

ALKAKLEEN

Heavy Duty Alkaline Cleaner

5711



DESCRIPTION

ALKAKLEEN is an alkaline detergent cleaner, formulated for effective decarbonising, derusting and degreasing operations.

ALKAKLEEN quickly penetrates to remove burnt oils, fats, greases, carbonised deposits and rust from surfaces.

APPLICATIONS

ALKAKLEEN is recommended for food areas, caterings and food processing industries.

ALKAKLEEN provides effective cleaning and decarbonising of grillers, ovens, fryers, pans, and other food cooking apparatus.

ALKAKLEEN may also be used wherever stainless steel, cast iron or steel has been subject to rust, grease or carbon deposits in machining or storage.

PRODUCT BENEFITS

- Effective - powerful to remove all burnt deposits
- Fast action – no harsh scrubbing required
- 3 in 1 action - prevents immediate re-rusting
- Safe on steel, stainless steel, ferrous and non-ferrous metal.
- Rinse-free
- Contains biodegradable surfactant
- Economical

PHYSICAL PROPERTIES

Appearance	Liquid
Colour	Pale yellow
Density	1.18 ± 0.05
Alkalinity (%Na ₂ O)	13.4 ± 0.5

APPROVAL / CONFORMANCE



InS A8 Registered No.: 1796440



Perfectly suitable for HACCP programs
Halal Certificate No.: PRN16040005774

DIRECTIONS FOR USE

AS HEAVY DUTY ALKALINE CLEANER

Should be used in a hot bath.

Concentrations of 0.3 - 0.4% for light deposits and rust at 85-90°C .

Concentrations of 0.4 - 0.8% for heavy duty cleaning & rust deposits at 85-90°C.

AS GRILL AND OVEN CLEANER

As a general guide, mix **ALKAKLEEN** at 1:10 parts with water and use through an Applied Canyon sprayer.

1. Warm oven or hot plate to 40° C to 60° C.
2. Turn off.
3. Spray **ALKAKLEEN** in oven or on hot plate.
4. Leave surface for 20-30 minutes.
5. Where contamination is heavy, work in with brush.
6. Wipe off with wet rag.
7. Rinse surface clean.

STORAGE & SAFETY

Highly alkaline product. Avoid contact with skin and eyes. Wear protective clothing (apron) and suitable eye/face protection (glasses and gloves) when handling. In case of contact, immediately flush with running water for at least 15 minutes. Seek medical attention if effects persists.

For further information please refer to the Material Safety Data Sheet.

PACKAGING

Ref: OH-5711-J1..... Pail 5L x 4
Ref: OH-5711-O2..... Pail 25L
Ref: OH-5711-U2..... Drum 200L

WARRANTY

The information contained herein is presented without guarantee or warranty and the Seller disclaims any liability incurred from the use thereof. Nothing contained herein is to be construed as a recommendation for any use in a commercial process not controlled by the Seller, nor for a use which is in violation of any existing patent, foreign or domestic, or of applicable laws and regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS EXPRESSLY STATED IN SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.